

# Material Safety Data Sheet

## SunClean Radiator Coolant

### 1. Production Description

- **Product Name:** Radiator Coolant
- **Application of the substance:** Coolant
- **Supplier:**  
Sun Clean Cleaning Ind. LLC  
P.O. Box 41475,  
SHARJAH – UAE  
Tel: +971 (6) 535 20 60  
Fax: +971 (6) 534 90 35  
[www.sun-cleaning.com](http://www.sun-cleaning.com)

Product information:  
Tel: +971 (6) 534 90 25  
Email: [detergents@sun-cleaning.com](mailto:detergents@sun-cleaning.com)

### 2. Hazards identification

#### Potential Acute Health Effects:

Hazardous in case of ingestion. Slightly hazardous in case of

- Skin contact (irritant)
- Eye contact (irritant)
- Inhalation. Severe over-exposure can result in death.

#### Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH. MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Non-mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to kidneys, liver, central nervous system (CNS).

Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

### 3. Composition / information on ingredients

The product is a blend of the following components.

#	Ingredients	% vol
CAS: 107-21-1	Ethylene Glycol	94%
	Other ingredients	6%

### 4. First aid measures

#### Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention if irritation occurs.

# Material Safety Data Sheet

## SunClean Radiator Coolant

**Skin Contact:** Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops. Cold water may be used.

**Serious Skin Contact:** Not available.

**Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**Serious Inhalation:** Not available.

**Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

**Serious Ingestion:** Medical Conditions Aggravated by Exposure: Persons with pre-existing kidney, respiratory, eye, or neurological problems might be more sensitive to Ethylene Glycol. Notes to Physician: 1. Support vital functions, correct for dehydration and shock, and manage fluid balance. 2. The currently recommended medical management of Ethylene Glycol poisoning includes elimination of Ethylene Glycol and metabolites. Elimination of Ethylene Glycol may be achieved by the following methods: a. Emptying the stomach by gastric lavage. It is useful if initiated within < 1 of ingestion. b. Correct metabolic acidosis with intravenous administration of sodium bicarbonate, adjusting the administration rate according to repeated and frequent measurement of acid/base status. c. Administer ethanol (orally or by IV (intravenously)) or fomepizole (4-methylpyrazole or Antizol)) therapy by IV as an antidote to inhibit the formation of toxic metabolites. d. If patients are diagnosed and treated early in the course with the above methods, hemodialysis may be avoided if fomepizole or ethanol therapy is effective and has corrected the metabolic acidosis, and no renal failure is present. However, once severe acidosis and renal failure occurred, however, hemodialysis is necessary. It is effective in removing Ethylene Glycol and toxic metabolites, and correcting metabolic acidosis.

### 5. Fire and explosion

**Flammability of the Product:** May be combustible at high temperature.

**Auto-Ignition Temperature:** 398°C (748.4°F)

**Flash Points:** CLOSED CUP: 111°C (231.8°F).

**Flammable Limits:** LOWER: 3.2%

**Products of Combustion:** These products are carbon oxides (CO, CO<sub>2</sub>).

**Fire Hazards in Presence of Various Substances:**

Slightly flammable to flammable in presence of open flames and sparks, of heat. Non-flammable in presence of shocks.

**Explosion Hazards in Presence of Various Substances:**

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

**Fire Fighting Media and Instructions:**

SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

**Special Remarks on Fire Hazards:** Not available.

**Special Remarks on Explosion Hazards:**

Explosive decomposition may occur if combined with strong acids or strong bases and subjected to elevated temperatures.

### 6. Accidental release measures

**Small Spill:**

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

**Large Spill:**

Stop leak if without risk. Do not get water inside container. Do not touch spilled material. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Call for assistance on disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through

# Material Safety Data Sheet

## SunClean Radiator Coolant

the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

### 7. Handling and storage

#### Precautions:

Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents, acids, alkalis.

**Storage:** Keep container tightly closed. Keep container in a cool, well-ventilated area. Hygroscopic

### 8. Exposure Controls / Personal Protection

#### Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

#### Personal Protection:

Safety glasses. Synthetic apron. Gloves (impervious). For most conditions, no respiratory protection should be needed. However, if material is heated or sprayed and if atmospheric levels exceed exposure guidelines, use an approved vapor (air purifying) respirator.

#### Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

#### Exposure Limits:

STEL: 120 (mg/m<sup>3</sup>) [Australia] TWA: 100 (mg/m<sup>3</sup>) from ACGIH (TLV) [United States] CEIL: 125 (mg/m<sup>3</sup>) from OSHA (PEL)

[United States] CEIL: 50 (ppm) from OSHA (PEL) [United States] TWA: 52 STEL: 104 (mg/m<sup>3</sup>) [United Kingdom (UK)] Inhalation TWA: 10 (mg/m<sup>3</sup>) [United Kingdom (UK)] SKIN3 Consult local authorities for acceptable exposure limits.

### 9 Physical and chemical properties

<b>Physical state and appearance:</b>	Liquid. (syrupy)
<b>Odor:</b>	Odorless.
<b>Taste:</b>	Mild sweet
<b>Molecular Weight:</b>	62.07 g/mole
<b>Color:</b>	Clear Colorless.
<b>pH (1% soln/water):</b>	Not available.
<b>Boiling Point:</b>	197.6°C (387.7°F)
<b>Melting Point:</b>	-13°C (8.6°F)
<b>Critical Temperature:</b>	Not available.
<b>Specific Gravity:</b>	1.1088 (Water = 1)
<b>Vapor Pressure:</b>	.06 mmHg @ 20 C; .092 mmHg at 25 C
<b>Vapor Density:</b>	2.14 (Air = 1)
<b>Volatility:</b>	Not available.
<b>Odor Threshold:</b>	Not available.
<b>Ionicity (in Water):</b>	Not available.

# Material Safety Data Sheet

## SunClean Radiator Coolant

### 10. Stability and reactivity

**Stability:** The product is stable.

**Instability Temperature:** Not available.

**Conditions of Instability:** Excess heat, incompatible materials.

**Incompatibility with various substances:** Reactive with oxidizing agents, acids, alkalis.

**Corrosivity:** Non-corrosive in presence of glass.

**Special Remarks on Reactivity:**

Hygroscopic. Absorbs moisture from the air. Avoid contamination with materials with hydroxyl compounds. Also incompatible with aliphatic amines, isocyanates, chlorosulfonic acid, and oleum

**Special Remarks on Corrosivity:** Not available.

**Polymerization:** Will not occur.

### 11. Toxicological information

**Routes of Entry:** Absorbed through skin. Ingestion.

**Toxicity to Animals:**

Acute oral toxicity (LD50): 4700 mg/kg [Rat]. Acute toxicity of the vapor (LC50): >200 mg/m<sup>3</sup> 4 hours [Rat].

**Chronic Effects on Humans:**

CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH. MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. Non-mutagenic for bacteria and/or yeast. May cause damage to the following organs: kidneys, liver, central nervous system (CNS).

**Other Toxic Effects on Humans:**

Hazardous in case of ingestion. Slightly hazardous in case of skin contact (irritant, permeator), of inhalation.

**Special Remarks on Toxicity to Animals:**

Lowest Published Toxic Dose/Conc: TDL [Man] - Route: oral; Dose: 15gm/kg Lethal Dose/Conc 50% Kill LD50 [Rabbit] - Route: dermal; Dose: 9530 ul/kg

**Special Remarks on Chronic Effects on Humans:**

May cause adverse reproductive effects and birth defects (teratogenic) based on animal test data. No human data has been reported at this time. May affect genetic material (mutagenic)

**Special Remarks on other Toxic Effects on Humans:**

Acute Potential Health Effects: Skin: May cause skin irritation. May cause more severe response if skin is abraded. A single prolonged exposure is not likely to result in material being absorbed through skin in harmful amounts. Massive contact with damaged skin may result in absorption of potentially harmful amounts Eyes: Vapors or mist may cause temporary eye irritation (mild temporary conjunctival inflammation) and lacrimation. Corneal injury is unlikely or insignificant. Ingestion: It is rapidly absorbed from the gastrointestinal tract. Oral toxicity is expected to be moderate in humans due to Ethylene Glycol even though tests with animals show a lower degree of toxicity. Excessive exposure (swallowing large amounts) may cause gastrointestinal tract irritation with nausea, vomiting, abdominal discomfort, diarrhea. It can affect behavior/central nervous system within 0.5 to 12 hours after ingestion. A transient inebriation with excitement, stupor, headache, slurred speech, ataxia, somnolence, and euphoria, similar to ethanol intoxication, can occur within the first several hours. As the Ethylene Glycol is metabolized, metabolic acidosis and further central nervous system depression (convulsions, muscle weakness) develop. Serious intoxication may develop to coma associated with hypotonia, hyporeflexia, and less commonly seizures, and meningismus. 12 to 24 hours

### 12. Ecological information

**Ecotoxicity:**

Ecotoxicity in water (LC50): 41000 mg/l 96 hours [Fish (Trout)]. 46300 mg/l 48 hours [water flea]. 34250 mg/l 96 hours [Fish (bluegill fish)]. 34250 mg/l 72 hours [Fish (Goldfish)].

**BOD5 and COD:** Not available.

**Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

# Material Safety Data Sheet

## SunClean Radiator Coolant

**Toxicity of the Products of Biodegradation:** The products of degradation are less toxic than the product itself.  
**Special Remarks on the Products of Biodegradation:** Not available.

### 13. Disposal considerations

**Waste Disposal:**

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

### 14. Transport information

**DOT Classification:** Not a DOT controlled material (United States).

**Identification:** Not applicable.

**Special Provisions for Transport:** Not applicable.

### 15. Regulatory information

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the

European Inventory of Existing Commercial Chemical Substances.

p. 6

**Other Classifications:**

**WHMIS (Canada):** CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

**DSCL (EEC):**

R22- Harmful if swallowed. S46- If swallowed, seek medical advice immediately and show this container or label.

**HMIS (U.S.A.):**

**Health Hazard:** 1

**Fire Hazard:** 1

**Reactivity:** 0

**Personal Protection:** C

**National Fire Protection Association (U.S.A.):**

**Health:** 1

**Flammability:** 1

**Reactivity:** 0

**Specific hazard:**

**Protective Equipment:**

Gloves. Lab coat. Not applicable. Safety glasses.

### 16 Other information

**References:** Not available.

**Other Special Considerations:** Not available.

**Disclaimer:**

The above information is to the best of our knowledge, current, accurate, and complete based on information reasonably available to us as of the date of preparation of this form. However, it is the user's responsibility to determine the safety, toxicity and suitability for their own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by us to the effects of such use or on the safety or toxicity of this product. Nor do we assume any liability arising out of use by others of the product. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when exception conditions or circumstances exist or because of applicable laws or regulations.